MT578 PAGE 1 FRONT

MOEN

SPECIAL FINISHED BRASS
1/2" and 1" HANDLE EXTENSION KIT
TO CORRECT DEEP ROUGH-IN

	MOEN	MOENTROL
ANTIQUE BRASS	92507	92517
SATIN BRASS / POLISHED BRASS	92528	92538



TO DISASSEMBLE: Pry off handle cover.

1. Remove handle screw, handle washer, handle bushing and handle knob.
2. Remove escutcheon screws, escutcheon and stop tube.

TO INSTALL EXTENSION:

3. Install extension adapter. Match with handle flats.
4. Install extension stop tube with collar out.
5. Replace escutcheon with long screws.
6. Re-install handle washer, handle bushing and handle knob using long screw.
7. Replace handle cover.

MOEN

Copyright
Moen Group, 1995
Printed in U.S.A.
MT-578-12-85

MOEN

SPECIAL FINISHED BRASS
1/2" and 1" HANDLE EXTENSION KIT
TO CORRECT DEEP ROUGH-IN

ANTIQUE BRASS 92507 92517
SATIN BRASS / POLISHED BRASS 92528 92538



TO DISASSEMBLE: Pry off handle cover.

1. Remove handle screw, handle washer, handle bushing and handle knob.
2. Remove escutcheon screws, escutcheon and stop tube.

TO INSTALL EXTENSION:

3. Install extension adapter. Match with handle flats.
4. Install extension stop tube with collar out.
5. Replace escutcheon with long screws.
6. Re-install handle washer, handle bushing and handle knob using long screw.
7. Replace handle cover.

MOEN

Copyright
Moen Group, 1995
Printed in U.S.A.
MT-578-12-85