

MOEN® 摩恩

花洒



文中图片仅供参考
(款式因型号而异)

如需安装支持, 配件丢失等, 请联系MOEN。
对于中国大陆以外的市场, 请咨询当地经销商。

(中国大陆) 400-630-8866

(中国大陆) www.moen.cn

(中国大陆以外) www.moen.com.hk

©2023 Moen Incorporated

注意事项:

MOEN® 摩恩卫浴产品以精湛的技术造而成, 保证品质优良, 美观耐用。
清洁产品时须小心, 避免对产品表面造成损害。
请用清水或中性的清洁剂清洁产品表面, 然后以柔软的毛巾抹干;

切勿使用含化学成分或腐蚀性的清洁剂、粗糙的布料抹擦。

建议定期清洗产品, 以保证其外观光洁明亮。
使用酸性清洁剂清洗附近物品时, 有可能损害产品表面, 请加倍小心。

安装前注意事项

- 本产品已经出厂检测及调试, 请勿自行拆卸。
- 安装前请彻底冲洗供水管以清除管道中的杂质。
- 推荐工作压力: 0.2~0.5Mpa (2~5bar)。花洒的最高工作压力: 0.5Mpa (5bar)。水压超过 0.5Mpa (5bar) 须安装减压阀。
- 花洒最高工作温度及环境温度: 60° C。请特别注意花洒须远离加热器, 否则可能损坏花洒, 甚至对使用者造成伤害。

推荐安装工具




安装步骤

1. 将花洒臂末端外螺纹缠上生胶带, 将花洒臂拧紧在供水管上, 确保花洒臂上的螺纹有足够的长度旋入供水管中, 保证花洒臂有足够强度挂起花洒。
2. 在花洒臂的另一头也要缠上生胶带, 再把花洒装上, 确保不漏水。

注意:

- 须确保供水管要足够牢固以支撑花洒。
- 图示仅供参考, 以实物为准。




清洗说明

如何清除出水口水垢:

出水孔在使用一段时间后可能会堆积杂质或结垢, 导致水流变形、流量减小。请打开水源, 用力按压和摩擦橡胶出水孔, 可以轻松将杂质或结垢清除。

如何清洁花洒:

- 为保持花洒洁净, 请定期清洁。
- 先用清水或中性的液体清洁剂清洗, 再用干净的软布彻底擦干整个表面。
- 切勿使用任何具有酸性和研磨作用的清洁剂。
- 禁止使用钢丝球、钢丝刷等硬质物品清洗, 以免划伤产品外表面。



单位: mm

产品售后保修条款

摩恩产品是在质量标准及生产工艺下制造的, 摩恩承诺为消费者购买的洁具产品提供有期限免费保修及终身维修服务。

花洒免费保修期为1年, 均自消费者购买日 (以摩恩产品分销商开具的发票或收据上载明日期为准) 起计。

免费保修范围为产品及产品配件由于材质及工艺原因而造成的故障或损坏。免费保修期内, 我们将无偿为您提供修理服务及更换发生故障的产品或产品配件。摩恩的售后服务责任仅限于对故障产品的修理, 而不延及您因产品故障而发生的其他损失, 法律另有规定的除外。

您需了解: 产品外观碰伤、刻划痕迹, 以及滥用及不正当保养所导致的故障或损坏, 均不属于免费保修范围。即使在免费保修期内, 属下列

(1) - (5) 情况之一的, 需酌情收取修理费用:

1. 不能出示相符的保修卡和有效购买凭证情况的,
2. 未按使用说明告知的使用方法和注意事项造成的故障,
3. 自行拆卸、维修、改装所造成的故障和损坏,
4. 由于不可抗力等外部原因引起的故障和损坏,
5. 由于运输、搬运、挤压等造成的损坏。

对于保修期外或不在保修范围内的产品, 如需维修, 摩恩将酌情收取上门费、人工费及材料费。本保修条款仅对原始消费者和酒店行业的购买者有效, 并不适用于本产品工业, 商业, 贸易和非酒店行业的使用。

如对本保修条款内容有任何疑问, 请拨打400 630 8866 咨询热线, 或向当地分销商咨询。对于中国大陆以外的市场, 此产品的保修及保障服务详情请咨询当地经销商。

摩恩公司对摩恩保修拥有最终解释权。

MOEN® 摩恩

合格证
Compliance Certification

产品名称 花洒
Product Name Showerhead

检验员
Inspector

生产日期
Date of Production

富俊汇康科技(上海)有限公司
中国(上海)自由贸易试验区新杨公路
1800弄1号4幢207室
邮编: 201413

Fortune Brands Innovations (Shanghai) Co., Ltd.
Room 207, Building 4, No. 1, Lane 1800, Xinyang Highway,
China Shanghai Pilot Free Trade Zone

MOEN® 摩恩

Showerhead



The pictures in the text are for reference only
(The style varies by model)

PLEASE CONTACT MOEN FIRST
For Installation Help, Missing or Replacement Parts.
For markets exclude Chinese mainland, please
consult your local dealer.
(Chinese Mainland) 400-630-8866
(Chinese Mainland) www.moen.cn
(Exclude Chinese Mainland) www.moen.com.hk
©2023 Moen Incorporated

CAUTIONS:

MOEN® 摩恩 Bathroom products are made with superb technology to ensure high quality, beautiful and durable. Be careful when cleaning the product to avoid damage to the surface of the product. Please clean the surface of the product with water or neutral detergent, and then dry it with a soft towel;


Do not use chemical or corrosive cleaners or rough cloths.

It is recommended to clean the product regularly to ensure its appearance is bright and clean. When using acidic cleaners to clean nearby items, it may damage the surface of the product. Please be extra careful.

Precautions before Installation

- The product have been passed the functionality test before ex-factory, please do not dismantl by yourself at will.
- Flush the water supply pipes thoroughly for remove debris.
- Recommendation working pressure: 0.2~0.5MPa(2~5Bar); The highest working pressure for showerhead is 0.5MPa(5Bar). If it exceeds 0.5MPa(5Bar), a pressure reducer is needed.
- The highest water and environment temperature is 60°C. Please keep showerhead away from heater, or it may become damaged and cause injury to the user.

Recommended Tools




Installation Instructions

1. Apply tepe on tape to the both end of shower arm. Thread shower arm into supply pipe, make sure there is enough length of fit so that the shower arm is strong enough to hang up the shower head.
2. Assemble the shower head, make sure there are no leaks.

NOTES:

- Ensure the supply line is deep-set enough for hanging up the showerhead.
- The picture is only for your reference. Please take the object as the standard.



Cleaning Instruction

How to Clean the Nozzles:

Any debris or mineral build-up may cause the flow stream to become distorted or reduce the flowrate. To remove the debris or mineral build-up, run water through the Handheld Shower, firmly press or rub your finger back and forth across the rubber nozzles.

How to Clean the Shower Body:

- Keep the product clean with clean water or mild liquid detergent regularly.
- Rinsed up with clean water or mild liquid, and then wiped dry with soft cloth.
- Acid or abrasive detergents are prohibited.
- Do not clean the product with hard material, for example: steel wool, scourer, etc.

MOEN LIMITED WARRANTY

We offer limited warranty and lifetime maintenance for Moen products, which are all manufactured with high standards of workmanship. The period of warranty shall start from the date of purchase of the product (according to the invoice or receipt issued by Moen distributors) and shall cover a period of the following: the warranty period for showerhead accessory is 1 year. This warranty is your coverage against material and workmanship malfunction or defects in Moen products or components. During the warranty period, we offer free main tenance and changing of malfunctioned products or product components. Moen's after sales service liability is limited to the maintenance of faulty items and does not cover your other losses caused by product malfunction, except for other wise stipulated by law. Cosmetic damages (scratches, dents, etc.) and malfunction or defects caused by abuse or improper maintenance is not covered by this warranty. Although the warranty period remains valid, in case of the following conditions (1) - (5), the maintenance cost (material cost and labor cost) shall still be charged as the case may be:

1. Corresponding warranty card and valid invoice cannot be presented;
2. Faults were caused by the incompliance with the instructions and precautions provided in the user's manual;
3. Damages and faults were caused by self-actuated dismantling, repair and refit;
4. Faults and damages were caused by external factors such as force majeure;
5. Damages were caused by transportation, unloading and extrusion, etc.

This warranty is valid for the original consumers only (including hotel use), and excludes industrial and commercial use of the product (except for hotel use). This card is only responsible for product main tenance rather than any other liabilities. In the event that the product requires maintenance but exceeds the warranty period, or that the product is not covered by this warranty, labor the product is not covered by this warranty, labor cost and material cost shall be charged as the case may be. Please call 400-630-8866 or contact local dealer for any question. For markets outside of Chinese mainland, the terms and conditions of warranty shall differ between product categories and countries. Please refer to warranty stated by local distribution. Moen Incorporated shall have the final interpretation of Moen warranties.

MOEN 摩恩

合格证
Compliance Certification


产品名称 花洒
Product Name Showerhead

检验员
Inspector

生产日期
Date of Production

富俊汇康科技(上海)有限公司
中国(上海)自由贸易试验区新杨公路
1800弄1号4幢207室
邮编: 201413

Fortune Brands Innovations (Shanghai) Co., Ltd.
Room 207, Building 4, No. 1, Lane 1800, Xinyang Highway,
China (Shanghai) Pilot Free Trade Zone



Unit: mm