




Buy it for looks. Buy it for life.®

Specifications



Aquasuite® Under Sink Water Filtration System

Models: 77200 series

NOTE: DESIGNED TO INSTALL THROUGH A 1-1/4" HOLE DIA.

FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing
- Carbon block filter technology
- Electronic filter life indicator takes standard 2032 watch battery (included)

OPERATION

- Lever style handle
- Will operate with less than 5 lbs. of force

Operating Specification

- Capacity: ChoiceFlo™ 9500/9600 Filter certified for up to 750 gallons (2,839 L)
- Pressure requirements: 20-125 psi (0.7-8.6 bar), non shock
- Temperature: 35-100°F (2-38°C)
- Flow Rate: 1 gpm (1.89 Lpm)

FLOW

- Filtered flow is limited to 1 gpm

CARTRIDGE

- 1224 cartridge design
- Nonmetallic/nonferrous and stainless steel material

STANDARDS

Faucet:

- Third party certified to CSA B-125.1, ASME A112.18.1, including NSF 61/9 and all applicable requirements referenced therein
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act (APMO PS49, NSF 42 & 53, Section 9)

- **ADA**  for lever handles

Filter:

- ChoiceFlo™ 9600
- Complies with NSF/ANSI Standard 42 for the reduction of chlorine, taste and odor

WARRANTY

Faucet/Under Sink Filtration System:

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year limited warranty if used in commercial installations

Filter:

- 30 day limited warranty on manufacturer's defects to the original consumer purchaser

