



Buy it for looks. Buy it for life.®

**FAUCET DESCRIPTION**

- Metal construction with chrome plated finish
- Pressure balancing cycle valve design with an adjustable temperature limit stop
- 1/2" IPS/CC connections
- Includes valve, showerhead, tub spout, arm and flange

**OPERATION**

- Lever style handle
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to ± 3° F (± 2° C)

**FLOW**

- Showerhead is limited to 2.0 gpm (7.6 L/min), maximum 1.5 gpm (5.7 L/min) at 45 psi

**CARTRIDGE**

- 1222 cartridge design
- Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations


**STANDARDS**

- Third party certified to meet ASSE 1016, ASME A112.18.1/ CSA B-125.1, and all applicable requirements referenced therein
- Meets Watersense® criteria
- ADA ♿ for lever handle
- Meets New York City Local Law No. 57

**WARRANTY**


- Limited lifetime warranty against leaks, drips, and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

# Specifications



**BAYHILL™**  
**Posi-Temp®**  
**Single-Handle Tub/Shower**

**MODEL: 82244HH**



**CRITICAL DIMENSIONS**

(DO NOT SCALE)