MOEN Buy it for looks. Buy it for life.®

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing
- Includes pop-up type waste assembly

OPERATION

- Lever style handles
- Hot side counterclockwise to open (clockwise to close)
- Cold side clockwise to open (counter-clockwise to close)

FLOW

Aerator is limited to 1.5 gpm max (5.7 L/min)

CARTRIDGE

- 1224 cartridge design
- Nonmetallic and stainless steel material

STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 ٠ and all applicable requirements referenced therein
- Contains no more than 0.25% weighted average lead content Certified to ANSI/NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe **Drinking Water Act**
- ADA (for lever handles •

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations
- NOTE
- *Service kits available for thicker or thinner deck applications. See Parts view.



Telford Two-Handle Lavatory Faucet

Models: 84988 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 3 HOLES, 1" MIN. DIA.

