# **MOEN**<sup>®</sup>

## **DESCRIPTION**

- Reflex<sup>™</sup> pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock® quick connect installation
- PowerClean Spray
- Flexible supply lines with 3/8"CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large pots while pull down wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout

## **OPERATION**

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

## **CARTRIDGE**


1255™ Duralast™ cartridge for Single-Handle Faucets

## **STANDARDS**


- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two inde pendently operating check valves, a primary and a secondary which prevent backflow
- ADA for lever handle

## WARRANTY

Lifetime limited warranty against leaks, drips, and finish defects to the original homeowner








**Edwyn™ Single Handle Pulldown Kitchen Faucet** Model: 87028 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2, 3 and 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)



Rev. 8/20