MOEN®

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Reflex[™] pulldown system offers smooth operation, easy movement and secure docking
- Duralock™ quick connect installation
- Three Power Clean™ attachments are designed to clean the hardest of hard-to-reach areas, where bottle brushes and sponges can't reach. The attachments work with the faucet's integrated Power Clean™ spray technology to spray off food particles, residue and grime.
- Each Power Clean™ attachment delivers a unique cleaning experience:
 - Targeted Spray A single, focused spray with precise, maximum force to chisel off stuck-on messes. Use on stubborn, troublesome areas, reach nooks and crannies, or use on narrow drinking/serving
 - Four-Corner Spray Four powerful sprays individually reach tight corners, but work together to forcefully remove and clean. Ideal for vases, water bottles and travel coffee mugs.
 - Broom Spray Five sprays create a full-sweeping aerated stream that clears larger areas within containers. Perfect for pitchers, carafes and large serving vessels.
- Pulldown spray with 68" braided hose
- 3/8" compression connections will accept standard ball nose connection for 3/8" tubing

OPERATION

- Lever style handle
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA (5) for lever handle
- The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation




Venango™ **Single-Handle High Arc Pulldown Kitchen Faucet**

Models: 87113 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2, 3 AND 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)

GREEN



FOR MORE INFORMATION CALL: 1-800-BUY-MOEN