MOEN[®]

DESCRIPTION

- PowerBoost[™] Spray Technology
- Reflex[™] pulldown system offers smoother operation, easy movement and secure docking
- Duralock[™] quick connect installation
- · Metal construction with various finishes identified by suffix
- · Pulldown spray with 68" braided hose
- 360° rotating spout
- · Flexible supply lines with 3/8" compression fittings

OPERATION

- · Lever style handle
- · Operates with less than 5 lbs. of force
- · Operates in stream or spray mode in the docked or retracted position

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- · Meets CalGreen and Georgia SB370 requirements
- · Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- · ADA for lever handle
- The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow

WARRANTY

- · Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation

Specifications



Mali™


Single-Handle High Arc Pulldown Kitchen Faucet

MODELS: 87561 Series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.

ADA 🕒

GREEN



CRITICAL DIMENSIONS DO NOT SCALE