# **MOEN**<sup>®</sup>

## Specifications

## **DESCRIPTION**

- · Metal construction with various finishes identified by suffix
- Flexible supply lines with 3/8" compression fittings
- With side spray
- Side Spray with direct connect onto valve body installation

### **OPERATION**

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Will operate with less than 5 lbs. of force

Aerator is limited to 1.5 gpm max (5.7 L/min)

## **CARTRIDGE**

- 1255™ Duralast™ cartridge
- Nonmetallic/nonferrous and stainless steel material


## **STANDARDS**

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements certified to NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe **Drinking Water Act**
- **ADA (** for lever handle

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations



Adler™ **Single-Handle Lever Kitchen Faucet** with Side Spray in Deck Plate

Model: 87605 series

**NOTE: DESIGNED TO INSTALL THROUGH** 3 HOLES 1-1/4" (32mm) MIN. DIA. AND 4" (102mm) ON CENTER

