# MOEN

# Specifications

# Buy it for looks. Buy it for life.®

#### FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- Hydrolock<sup>®</sup> quick connect installation
- Pullout spray with 68" braided hose
- Flexible supply lines with 3/8" compression fittings
  High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout provides ability to install handle on either side

#### OPERATION

- Lever style handle
- Operates in stream or spray mode in the pullout or retracted position
- When filling a vessel outside the sink, the pause feature conveniently stops the water flow as the wand passes over the counter top
   Temperature controlled by 100° arc of handle travel
- FLOW

Flow is limited to 2.2. gpm (8.3 L/min) at 60 psi

CARTRIDGE


• 1255<sup>™</sup> Duralast<sup>™</sup> cartridge for Single-Handle Faucets

#### STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act
- The backflow protection system in the device consists of two independently
  operating check valves, a primary and a secondary which prevent backflow
- ADA ( for lever handle

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



# 90 DEGREE™ Single Handle High Arc Pull Out Kitchen Faucet

### Model: CA7597 series

## **NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/2" (38mm) DIA.

