MOEN®

DESCRIPTION

- •Reflex[™] pulldown system offers smoother operation,
- easy movement and secure docking
- PowerBoost[™] Spray Technology
- Duralock ${}^{\rm TM}$ quick connect installation
- Metal construction with various finishes identified by suffix
- Pulldown spray with 68" braided hose
- High arc spout provides height and reach to fill or clean large pots while
- pullout wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout
- Flexible supply lines with 3/8" compression fittings

OPERATION

- •Lever style handle
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position
- \bullet Temperature controlled by 100 $^\circ$ arc of handle travel

FLOW

• Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials **STANDARDS**
- Third party certified to IAPMO Green, ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 & with
- the Federal Safe Drinking Water Act
- ADA for lever handle
- The backflow protection system in this device consists of two independently
- operating check valves, a primary and a secondary which prevent backflow

WARRANTY

• Lifetime limited warranty against leaks, drips and

finish defects to the original homeowner

- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations





Meena™

Single-Handle High Arc Pulldown Kitchen

MODELS: 87270 Series

THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, OR 3 HOLES, 1-1/2" (38MM) MIN. DIA.





SYDNO31128

PC23I04

02/08/2022 Seleased 00