# **MOEN**®

## **SPECIFICATIONS**

#### **DESCRIPTION**

- Reflex<sup>™</sup> pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with Spot Resist<sup>™</sup> finish
- Duralock™ quick connect installation
- Power Boost™ Technology provides boosted water performance with the push of a button
- Pulldown spray with 68" braided hose
- Flexible supply lines with 3/8" CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout

#### **OPERATION**

- Lever style handle
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

#### **FLOW**

• Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

#### **CARTRIDGE**

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials

#### **STANDARDS**

- Third party certified to IAPMO Green, ASME A112.18.1/ CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handles
- The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations




### Durani™

Single-Handle High Arc
Pull Down Kitchen Faucet

MODELS: 87070 Series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2, 3 AND 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)





CRITICAL DIMENSIONS DO NOT SCALE