MOEN[®]

SPECIFICATIONS

DESCRIPTION

- Reflex[™] pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock® quick connect installation
- PowerBoost[™] Spray Technology for more force, less splash
- Pullout spray with 68" braided hose
- Flexible supply lines with 3/8" CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout **OPERATION**

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position FLOW

• Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi


CARTRIDGE

• 1255™ Duralast™ cartridge for Single-handle Faucets

- **STANDARDS** • Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein, including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA 🕭 for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations



Maureen™

Single-handle Pulldown Kitchen Faucet

MODELS: 87493 Series

NOTE: This faucet is designed to be Installed through 1 or 3 holes, 1-1/2" min. Dia.



