MOEN®

SPECIFICATIONS

DESCRIPTION

- Reflex™ pulldown system offers smoother operation, easy movement and secure docking
- Powerclean[™] Spray Technology for more force, less splash
- Duralock™ quick connect installation
- Metal construction with various finishes identified by suffix
- Pulldown spray with 68" braided hose
- This retro fit kit is compatible with Moen pulldowns that were purchased during the following time period: January 2022 to current.
- Compatible with F9800 Advanced Filtration System, or F9900 Reverse Osmosis with Air Gap 105895 Series (Sold Separately)

OPERATION

- Three function spray wand: unfiltered stream, unfiltered powerclean spray and filtered laminar stream
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi for unfiltered water
- Flow is 0.7 gpm (2.6 L/min) for filtered water

STANDARDS

- Stated product certifications and approvals are valid only when used with compatible Moen pulldown faucet specified in description.
- Third party certified to ASME A112.18.1/CSA-B125.1 and all applicable requirement referenced therein including NSF61/9 & 372
- Certified by IAPMO R&T to NSF/ANSI 372 for Low Lead Content and NSF/ANSI 42, 58, and CSA B483.1 for material safety and structural integrity requirements
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations



Modern™

3-in-1 Water Filtration Pulldown Kitchen Faucet Retrofit Wand/Hose Kit

MODELS: F26660 Series



CRITICAL DIMENSIONS DO NOT SCALE

PC25361

0.14/2024 Schasol 00