MOEN®

SPECIFICATIONS

DESCRIPTION

- Power Boost™ Spray Technology
- Reflex[™] pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with Spot Resist Stainless[™] finish
- Duralock™ quick connect system
- Pulldown spray with 68" braided hose
- Flexible supply lines with 3/8" compression fittings and optional 1/2" adapters
- High arc spout provides height and reach to fill or clean large pots while pull down wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout

OPERATION

- Lever style handles
- Temperature controlled by 100 arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the docked or retracted position

• Flow is limited to 1.5 gpm (5.7L/min) at 60 psi

CARTRIDGE

1255 Duralast™ Cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA (for lever handles
- The backflow protection system in the device consists of two independently operating check valves, a primaryand a secondary which prevent backflow

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation



Iriza™

Single Handle Pulldown Kitchen Faucet

7929 Series MODELS:

NOTE: This faucet is designed to be installed through 1 or 3 holes, 1-1/2" min dia.

