

DESCRIPTION

- Magnetix™ technology allows wands to return effortlessly for secured docking every time
- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock® quick connect installation
- PowerClean Spray
- Flexible supply lines with 3/8" CC fittings connect directly to supply stop
- High arc spout provides height and reach to fill or clean large pots while pull down wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout

OPERATION

- Lever style handle
- Temperature controlled by 90° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous and brass materials
- Single body construction for easy replacement


STANDARDS

- Third party certified to IAPMO Green, ASME A1 12.18.1 /CSA B125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ♿ ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips, and finish defects to the original homeowner

Visit ww.moen.com/support for complete details and limitations



**Georgene™ Single Handle
Pulldown Kitchen Faucet**
Model: 87923 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 or 3 HOLE, 1-1/2" (38mm) MIN. DIA.

