

DESCRIPTION

- A flexible hose system that offers secure docking, smooth operation, and easy movement
- Metal construction with various finishes identified by suffix
- PowerClean™ Spray Technology
- Durlock® quick connect installation
- Pullout spray with 68" braided hose
- Flexible supplies with 3/8" compression fittings

OPERATION

- Lever style handle
- Temperature controlled by 120° arc of handle travel
- Spout rotation is 120°
- Operates with less than 5lbs. of force
- Operates in stream or spray mode in the pullout or retracted position


FLOW

- Aerator is limited to 1.5 gpm (5.7 L/min) max.

CARTRIDGE

- 1255 cartridge design
- Engineered polymers, non-ferrous and stainless steel materials

STANDARDS

- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- Third party certified to meet CSA B125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Meets CalGreen and Georgia SB370 requirements
- ADA  for lever handles
- The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
 - 5-year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations



STOKES™

Single Control Kitchen Faucet

MODELS: 87144 Series

**NOTE: DESIGNED TO INSTALL
IN 1 OR 3 HOLES 1-1/2" (38mm) DIA.**

