

## DESCRIPTION

- Various finishes identified by suffix
- Ocean recycled plastic dock
- Magnetix™ technology features an innovative magnetic docking system
- Includes rainshower, handshower, hose and magnetic docking system
- 60" double interlock spiral metal hose (for 216C1EP series)
- 72" double interlock spiral metal hose (for 216C3 series and 216C3EP series)
- 1/2" IPS connections
- Assembled with 2 check valves for backflow prevention

## OPERATION

- 3-way diverter provides ability to flow each shower head separately or combined for more coverage
- Pause/trickle function allows to momentarily pause the handshower flow
- Engineered ball joint enables smooth, precise showerhead articulation for effortless adjustment and accurate spray targeting

## FLOW

- Designed to deliver 2.5 gpm (9.5 L/min) MAX at 80 psi
- EP suffix models are limited to 1.75 GPM (6.6 L/min) MAX at 80 PSI

## STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1  
Consult your local building department for the specific installation requirements

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year limited warranty when used in a commercial installation
- 10 year limited warranty when used in a multifamily installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations



## MAGNETIX™ Plus

### Combo Shower with Magnetic Dock

**MODELS:** 216C1EP Series,  
216C3 Series, 216C3EP Series

