

DESCRIPTION

- Various finishes identified by suffix
- Magnetix™ technology features an innovative magnetic docking system
- Includes rainshower, handshower, hose and magnetic docking system
- 60" double interlock spiral metal hose (for 216D1EP series and 216D5EP series)
- 72" double interlock spiral metal hose (for 216D3 series and 216D3EP series)
- 1/2" IPS connections
- Assembled with 2 check valves for backflow prevention

OPERATION

- 3-way diverter provides ability to flow each shower head separately or combined for more coverage
- Pause/trickle function allows to momentarily pause the handshower flow
- Pivoting arm lowers handshower with integrated undock-button for additional spray coverage
- Engineered ball joint enables smooth, precise showerhead articulation for effortless adjustment and accurate spray targeting

FLOW

- Designed to deliver 2.5 gpm (9.5 L/min) MAX at 80 psi
- EP suffix models are limited to 1.75 GPM (6.6 L/min) MAX at 80 PSI

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1
Consult your local building department for the specific installation requirements

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year limited warranty when used in a commercial installation
- 10 year limited warranty when used in a multifamily installation
- Visit www.moen.com/support for complete details and limitations



MAGNETIX™ Plus

2-in-1 Shower with Magnetic Dock

MODELS

216D1EP Series,
216D3 Series, 216D3EP Series
216D5EP Series

