

## DESCRIPTION

- Various finishes identified by suffix
- Ocean recycled plastic dock
- Magnetix™ technology features an innovative magnetic docking system
- Includes handshower, hose and magnetic docking system
- 60" double interlock spiral metal hose  
*(for 216H1EP series)*
- 72" double interlock spiral metal hose  
*(for 216H3 series and 216H3EP series)*
- Assembled with 2 check valves for backflow prevention

## OPERATION

- Adjust lever on spray face to select desired spray function
- Pause|Trickle button located on handle

## FLOW

- Flowrate for non-EP models are limited to 2.5 gpm (9.5 L/min) max
- Flowrate for EP suffix models are limited to 1.75 gpm (6.6 L/min) max

## STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1,  
Consult your local building department for the specific installation requirements

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year limited warranty when used in a commercial installation
- 10 year limited warranty when used in a multifamily installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations



## MAGNETIX™ Plus

### Handheld Shower with Magnetic Dock

**MODELS:** 216H1EP Series,  
216H3 Series, 216H3EP Series

