

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Pressure balancing cycle valve design with an adjustable temperature limit stop
- 1/2" IPS connections
- Includes valve, tub spout, handshower and hose assembly

OPERATION

- Lever style handle
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to $\pm 3.6^{\circ}\text{F}$
- 5 Spray Functions: concentrated rinse; Full Spray; Invigorating spray massaging rinse; targeted massage

FLOW

- Shower wand is limited to 1.75 gpm

CARTRIDGE

- 1222 cartridge design
- Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations

STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- **ADA** for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10-year limited warranty when used in a multifamily installation
- 5-year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations



Alinde™

Single Handle Tub/Shower Valve with Handshower

MODELS:

82511 Series

