MOEN®

There is more than one version of this model. Page down to identify the version you have.

DESCRIPTION

- · Metal construction with chrome finish
- Includes showerhead, arm, flange and diverter spout

OPERATION

- Lever style handle with temperature red/blue indicator on the escutcheon
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to ± 3.6° F (±2° C)
- 6 function showerhead

FLOW

EP suffix models are limited to 2.0 gpm (7.6 L/min) max for products manufactured prior to June 30, 2018. EP suffix models manufactured after June 30, 2018 are limited to 1.75 gpm (6.7 L/min) max.

CARTRIDGE

- 1222 cartridge design
- · Nonmetallic/nonferrous and stainless steel materials
- · Accommodates back to back installations

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®
- ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations

2" CC (51mm) FACE OF STUD FINISHED WALL LINE 2-1/2" MAX. (63mm) 4-1/2" (114mm) 6'-6" WALL OPENING INLET COLD -3/8" (35mm) M 7-1/2" (191mm) 45" (1143mm)/ 48" (1219mm)-SHOWER 32" (813mm)-TUB OR TUB SHOWER (179mm) TUB RIM FLOOI

Specifications



Genta™ POSI-TEMP® Single-Handle Tub/Shower Trim Kit


Models: T2471 series - valve trim only


T2472EP series - shower trim only T2473EP series - tub/shower trim only

NH - No Showerhead included

Valves: 62300 series

2500 series





CRITICAL DIMENSIONS

(DO NOT SCALE)



MOEN[®]

DESCRIPTION

- · Metal construction with chrome finish
- Includes showerhead, arm, flange and diverter spout

OPERATION

- Lever style handle with temperature red/blue indicator on the escutcheon
- · 3 function showerhead: full, wide and massage
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- · Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to ± 3.6° F (±2° C)

FLOW

EP suffix models are limited to 2.0 gpm (7.6 L/min) max for products manufactured prior to June 30, 2018. EP suffix models manufactured after June 30, 2018 are limited to 1.75 gpm (6.7 L/min) max.

CARTRIDGE

- 1222 cartridge design
- · Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®
- ADA for lever handle

WARRANTY

 Lifetime limited warranty against leaks, drips and finish defects to the original homeowner

> 2" CC (51mm) -7/8" IPS (48mm) MAX WALL

FINISHED WALL LINE

WALL OPENING

COLD

(179mm)

TUB RIM

FACE OF STUD

2-1/2" MAX. (63mm)

-3/8" (35mm)

45" (1143mm)/ 48" (1219mm)-SHOWER 32" (813mm)-TUB OR TUB SHOWER 6'-6"

- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations

Specifications




Genta™ POSI-TEMP® Single-Handle Tub/Shower Trim Kit


Models: T2471 series - valve trim only

T2472EP series - shower trim only T2473EP series - tub/shower trim only

Valves: 62300 series

2500 series









7-1/2"

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN