

**DESCRIPTION**

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections
- Duralock™ quick connect system
- Include pop-up waste assembly

**OPERATION**

- Cold side clockwise to open (counterclockwise to close)
- Hot side counterclockwise to open (clockwise to close)
- Lever-style handles

**FLOW**

- Water usage is limited to these maximum flow rates as indicated by the corresponding product markings
- 1.2 gpm max (4.5L/min) at 60 psi

**CARTRIDGE**


- 1234™ Duralast™ cartridge
- Nonmetallic and stainless steel material

**STANDARDS**

- Third party certified to WaterSense®, ASME A112.18.1/CSA B125.1, and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- Products marked with 1.2 gpm are compliant with California water efficiency regulations
- ADA for lever handles

**WARRANTY**

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations

**Align™**

Two-Handle Widespread Lavatory Faucet

**MODEL:** TV6193 Series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 3 HOLES, 1-1/8" MIN. DIA.  
FOR DECK THICKNESS 1-1/2" TO 3", USE SERVICE KIT #175709. VALVES INSTALL THROUGH 1-1/4" DIA. HOLE.

